

Centurion *EasyGate LX*



Key Benefits

More Secure

- A range of barrier height options 1200mm / 1800mm
- Fast acting barriers close behind authorised users to deter tailgating
- IR sensors detect tailgating and unauthorised entry

Faster Throughput

- Fast acting barriers
- Quiet, smooth mechanism

High End Aesthetics

- Stainless steel pedestal design
- Easily customisable decorative tops to blend in with the building design

Advanced Technology

- Auto diagnostic function
- Bespoke PC based control set up

Reliable

- MTBF of 3,000,000 operations

Applications

- Corporate Offices, Government, Sports Stadia, Leisure Clubs, Manufacturing Plants

Concept

The Centurion EasyGate is the very latest in high tech entrance control systems and is designed to ensure only one person gains access for each authorised card presented. The EasyGate uses glass barriers in conjunction with optical tailgate detection technology to provide a high throughput / high security gate. The glass barriers are designed to work in a normally closed mode and retract inside the pedestal after a valid card has been presented giving the authorised user a clear lane to pass through. The barriers quickly close behind the authorised person, thereby deterring any unauthorised entry or tailgating.

EasyGate automatically sounds a local alarm if someone enters without authorisation additionally a relay can activate stricter security actions such as triggering CCTV, locking doors, or controlling elevators.

EasyGate barriers feature variable torque and speed settings to tailor the units to specific applications. Safety beams monitor the area near the barriers and deter the barriers from closing on an obstruction. Additionally, the barriers feature a torque sensor and retract if

DDA Compliant

The Centurion EasyGate comes in 2 pedestal widths to provide for a lane width of either 550 mm for standard access or 900mm for disabled access. Alternatively the EasyGate can be installed along side a Centurion SwingGate which can allow for gaps of up to 2 meters to be secured to facilitate deliveries.

Authorisation

The Easygate can be integrated with any access control system and users can be authorised by a variety of means such as proximity cards, biometrics, barcodes, swipe guards as well as having the capability to allow for manual override by the security or reception team.

Accessories

The EasyGate has a number of accessories to optimise the system configuration.

Displays

The EasyGate has options for displays by the card reader and on the end of the lane to simplify its use and speed up throughput

Decorative Tops

The top of the EasyGate can be finished in a variety of different materials to help blend pedestal in with the building fabric design

Back Up

The system can be supplied with an accumulator, designed to ensure the barriers open on power fail

Infill System

There are a variety of different infill systems to help create the secure perimeter design and guide users through the lanes.

Remote Control

A variety of different remote control systems can be provide to enable guards to override some of the facilities of the system and to facilitate visitor entry by the reception team.

About CENTAMAN

CENTAMAN Systems Pty is the exclusive distributor for some of the world's most prestigious entrance control brands that are used to protect leading corporations, governments, leisure and education facilities as well as retailers around the globe. The products highlighted here are some of the key products that make up the CENTAMAN portfolio of entrance control solutions.

With over 14 years experience successfully delivering entrance control solution and over 40 staff and operates 5 offices throughout Australia and New Zealand CENTAMAN is the ideal choice of partner for all your entrance control requirements. CENTAMAN offers supply only to full turnkey installation projects and has a variety of flexible support and maintenance options to ensure the ongoing reliable operation of your entrance control solution all backed by a Sydney based 24/7 support telephone support helpline.

For more information contact CENTAMAN Systems.

Head Office Sydney 127 Alexander St, Crows Nest NSW 2065, Australia **Tel** +61 2 9906 7522

Email turnstiles@centaman.com.au **Web** www.centaman.com.au

Melbourne +61 3 9530 6830 **Perth** +61 8 9345 3599 **Brisbane** +61 7 3852 2535 **New Zealand** + 64 9 579 4600

Specifications subject to change without prior notice

they detect an object when closing. When integrated with the fire alarm system and upon a fire alarm, the barriers

Specification

Dimensions

Standard: 1700mm(L) x 320mm(W) x 990mm(H)

Wide: 1700mm(L) x 500mm(W) x 990mm(H)

Barrier Height 1200mm/ 1800mm

Lane width 550mm / 900 mm

Gap Between barriers: 80mm

Electrical

Power Supply : 12 V DC

Current : Standby 0.4 A

Consumption : Operational 6 A

Operating Temp : -10°C to 50°C (with heater)

Motor : 12 V DC

Operation

Mode : Normally Closed

Control : Card In / Card Out

Card In / No Exit

Card In / Free Exit

Locked

Free Passage

Pictograms : Wait Mode (Yellow Arrow)

Access Granted (Green Arrow)

Illegal Transaction (Red Cross)

Materials

Panel : 8 mm Tempered Safety Glass

Top Cover : Stainless Steel (other options)

Front Cover : Stainless Steel

Side Panels : Stainless Steel

Frame : Steel